On/off electrothermic actuators Series 22C



Main features

- 22C series available in the following versions : NA (Normally open) NC (Normally closed)

- 2-wire (Standard)
- 4-wire (With auxiliary contact)New compact design.

- Availability to check status of actuator (On/off) by transparent window on the cover
- CE Marked in accordance with the following
- EEC EMC (CEI-EN 55104/95; CEI-EN55014/93), EMC directive EN 60730-1; EN 60730-2-14, low voltage directive
- ENEC approved .

BHUTORIA

Bhutoria Airconditioning Pvt Ltd

340/2722, Motilal Naga #2 Link Road, Opp Bangur Nagar Goregaon (W), Mumbai 400090 India Tel +91 22 2878 8849 Email: info@bria.net.in www.bria.net.in



Fan-coil valves Series 2131 - 3131 - 4131



Main features

Complete range in the following versions:

- 2-way DN: 1/2", 3/4", 1" 3-way DN: 1/2", 3/4", 1" 3-way with 4 ports DN: 1/2", 3/4"
- The 3-way version and the 3-way versions with 4 ports can be used as diverting or mixing valves of compact size and reduced weights. The valves are motorized with actuators series 22C or actuators with stroke 2.5 mm with ring nut M30x1.5.



A Division of Watts Water Technologies Inc.